

PA SPEAKER



Column Speaker

Inter-m column speakers provide a clean and dedicated design with rich sound quality and are used for indoor/outdoor announcement and BGM. A variety of line-ups can be easily adopted in any type of user environment depending on power and size

CS-SERIES

- High quality sound
- Simple and unique design
- Easy and time saving installation
- Angle adjustment by mounting bracket
- Speaker terminal (800 series)



CS-410/420/430/440/510/520/530/540



CS-810/820/830/840



CU-410/420/430/440

CU-400/500 SERIES

- High quality sound
- Simple design with rounded corners and edges
- Easy and time saving installation
- Angle adjustment by mounting bracket



CU-510/520/530/540

CU-900 SERIES

- Top quality tweeter is used
- Detail and rich sound quality
- Strong aluminum frame
- Easy and time saving installation
- Angle adjustment by mounting bracket
- Speaker terminal



CU-910(V)/920(V)/930(V)/940(V)/
920HV/940HV



Inter-m ceiling speakers provide a natural and smooth sound with a variety of mounting and fit to any places that announcements and BGM required such as buildings, apartments, hotels and etc. It has variety of line-up from 1W APT series to 2way type high powered speaker.

Ceiling Speaker

APT SERIES

- Clean and clear sound reproduction
- A design harmonized with interior decoration
- Easy installation on ceiling or wall



APT-01A



APT-01C/03C



APT-01R



APT-01W/03W

CS SERIES

- High quality sound
- Easy installation on the ceiling
- Multi-tap for different setting



CS-03/03A/05 CS-3/6/12
CS-20/30/80 CS-10/44/45



CS-10/44/45

MS SERIES

- High quality sound
- Installation can be done without any tool
- Solid structure and material



MS-03A



MS-15/30



Wall Speaker

Inter-M wall speakers are ideal for BGM playback and also offer precise voice reproduction. Our new articulated mounting bracket offers ease of installation with precision speaker orientation.



IWS-10(I/B)

IWS-10(I/B)

- High quality speaker unit
- Stylish and sleek design wall speaker
- A design adopted in modern sense



SWS-03/10(I/B)

SWS-3/10(I/B)

- High quality speaker unit produce detail and rich sound
- Stylish and sleek design wall speaker
- Harmonized with general structure when installed

WS-203(I/B)/210(I/B)/230(I/B)

- High quality speaker unit
- Stylish and sleek design
- Easy installation
- Outdoor speaker
- High reliability



WS-203(I/B)/210(I/B)/230(I/B)



CF-60/120(B/W)

CF-60/120(B/W)

- A outstanding design harmonized with interior decoration
- A coner design considering the spatial arrangement
- Built-in switchable impedance matching transformer
- 2 way speaker



Inter-M surface mounted speakers are manufactured using high-quality drivers and components. Our custom design and tuned crossover network ensures a smooth frequency responses and maximizes the SPL of the High-frequency and Low-frequency drivers.

Surface Mounted Speaker



FS-30N/60N/100N/52N

FS-30N/60N/100N

- High quality sound
- Dual circuit with high and low impedance
- Screw terminal for speaker line
- High quality transformer for long distance operation
- High-strength ABS Injection
- Mounting bracket included
- Safety ring included

GS-50N

- High quality sound
- Dual circuit with high and low impedance
- Screw terminal for speaker line
- High quality transformer for long distance operation
- High-strength abs injection
- Mounting bracket included
- Safety ring included



GS-50N

CI-40(T)/60(T)



CI-40(T)/60(T)

- Optimized sound quality on music playback & voice intelligibility
- Compact vented enclosure
- High quality transformer
- Circuit Protection
- Articulated Mounting Bracket
- Safety ring included



Horn Speaker

Inter-m horn speakers are commonly installed in commercial building, factories, schools, public areas, civic centers and so on because it has excellent intelligibility & Loudness, High directivity, Good reliability.



CH-522/532

CH-522/532

- High sound pressure and straightness
- Wide frequency range with remarkable vocal clarity
- Indoor or outdoor use
- Wide range of angle adjustment

HS-20/30/50/20RT/30RT/40RT

- High sound pressure and straightness
- Wide frequency range with remarkable vocal clarity
- Easy installation
- Highly reliable and high power horn driver unit
- Rated input and output sound pressure
- Size and weight



HS-20/30/50

HS-20RT/30RT/40RT

DRIVER UNIT

- High reliability and high powered HORN DRIVER UNIT
- Rated power and SPL
 - DU-30T : 30W, 8Ω/330Ω/660Ω, 110dB
 - DU-40T : 40W, 8Ω/250Ω/500Ω, 110dB
 - DU-50 : 50W 8Ω, 113dB
 - DU-75 : 75W 8Ω, 114dB
 - DU-100 : 100W 8Ω, 113dB
- Size and Weight
 - SH-317 : 317(W) x 205(H) x 290(D)mm
 - DU-30T : 114(Ø) x 120mm, 1.55Kg
 - DU-40T : 114(Ø) x 120mm, 1.75Kg
 - DU-50 : 120(Ø) x 90mm, 2Kg
 - DU-75 : 120(Ø) x 92mm, 2.65Kg
 - DU-100 : 117(Ø) x 102mm, 3.5Kg



SH-317



DU-30T



DU-40T



DU-50



DU-75



DU-100



SW-2200/2300

SW-2200/2300

- Exclusive material for speaker of sound system
- Inner conductor size
- Number of core wire
- Inner wire can be identified through the transparent insulator

FSB-3

- Angle adjustment (L/R, Up/Down)
- SOLID fixed ANGLE adjustment
- Safety ring included
- Screws included



FSB-3

FSB-1/FSB-2

- Small speaker mounting bracket
- Angle adjustment (L/R, Up/Down)



FSB-1



FSB-2

SB-1/2

- Stand for small and large speaker
- SHORT/LONG TYPE
- Single angle of beam spread
- Easily mounting on the wall or ceiling



SB-1



SB-2

TSS-1

- Stand for small and large speaker
- Maintain stability as a tripod



TSS-1

PA Speakers Specifications



Speaker type	Model	Type	Rated Power	Frequency Response	SPL	Impedance	Dimension(mm) <WxHxD>	
Column Speaker	CS-410	1 Way	10W	180Hz - 12KHz	91dB	1K Ω /2K Ω	159x300x115	
	CS-420		20W		94dB	500 Ω /1K Ω	159x400x115	
	CS-430		30W		95dB	330 Ω /660K Ω	159x500x115	
	CS-440		40W		97dB	250 Ω /500 Ω	159x600x115	
	CS-510		10W	180Hz - 12KHz	89dB	1K Ω /2K Ω	159x300x115	
	CS-520		20W		92dB	500 Ω /1K Ω	159x400x115	
	CS-530		30W		93dB	330 Ω /660K Ω	159x500x115	
	CS-540		40W		95dB	250 Ω /500 Ω	159x600x115	
	CS-810	2 Way	10W	150Hz - 20KHz	90dB	1K Ω /2K Ω	149x310x124	
	CS-820		20W		93dB	500 Ω /1K Ω	149x420x124	
	CS-830		30W		94dB	330 Ω /660K Ω	149x530x124	
	CS-840		40W		96dB	250 Ω /500 Ω	149x640x124	
	CU-410	1 Way	10W	180Hz - 14KHz	91dB	1K Ω /2K Ω	156x300x129	
	CU-420		20W		94dB	500 Ω /1K Ω	156x400x129	
	CU-430		30W		95dB	330 Ω /660K Ω	156x500x129	
	CU-440		40W		97dB	250 Ω /500 Ω	156x600x129	
	CU-510		10W		91dB	1K Ω /2K Ω	156x300x129	
	CU-520		20W		94dB	500 Ω /1K Ω	156x400x129	
	CU-530		30W		95dB	330 Ω /660K Ω	156x500x129	
	CU-540		40W		97dB	250 Ω /500 Ω	156x600x129	
	CU-910(V)	2 Way	10W	220Hz-15KHz/ 220Hz-18KHz(V)	87dB/88dB(V)	1K Ω /2K Ω	104x290x86	
	CU-920(V)		20W		89dB/91dB(V)	500 Ω /1K Ω	104x400x86	
	CU-930(V)		30W		91dB	330 Ω /660K Ω	104x490x86	
	CU-940(V)		40W		91dB	250 Ω /500 Ω	104x580x86	
CU-920H	20W		180Hz-15KHz	86dB	500 Ω /1K Ω	104x400x86		
CU-920HV			180Hz-18KHz	87dB				
CU-940H			180Hz-15KHz	87dB				
CU-940HV			180Hz-18KHz	88dB				
Ceiling Speaker	APT-01A(K)	1 Way	1W	300Hz-16KHz	82dB	8 Ω /10K Ω	120x120x15	
	APT-01C		1W	260Hz-10KHz	85dB	10K Ω	41(ϕ)x120(D)	
	APT-03C		3W	260Hz-12KHz	86dB	3.3K Ω	41(ϕ)x119(D)	
	APT-01R		1W	260Hz-10KHz	84dB	10K Ω	152(ϕ)x55(D)	
	APT-01W		1W	260Hz-10KHz	85dB	10K Ω	120x120x50	
	APT-03W		3W	260Hz-12KHz	86dB	3.3K Ω		
	CS-03		3W	100Hz-15KHz	90dB	3.3K Ω /5K Ω /10K Ω	228(ϕ)x96(D)	
	CS-03A		3W	150Hz-15KHz			227(ϕ)x100(D)	
	CS-05	5W	150Hz-14KHz	92dB	2K Ω /4K Ω /8K Ω	230(ϕ)x180(D)		
	CS-20	20W	200Hz-20KHz	88dB	500 Ω /1K Ω /2K Ω			
	CS-30	30W		90dB	330 Ω /500 Ω /1K Ω			
	CS-80	80W		88dB	125 Ω /250 Ω /500 Ω			
	CS-3	3W	250Hz-15KHz	88dB	3.3K Ω /5K Ω /10K Ω	230(ϕ)x100(D)		
	CS-6	6W					1.7K Ω /4K Ω /8K Ω	
	CS-12	12W					89dB	800 Ω /1K Ω /2K Ω
	CS-10	10W	120Hz-10KHz	92dB	1K Ω /2K Ω	303x303x95		
	CS-44	1 Way	3W	180Hz-10KHz	90dB		3.3K Ω /5K Ω /10K Ω	
	CS-55		3W	110Hz-14KHz				
	MS-03A	3W	110Hz-10KHz	90dB	3.3K Ω /5K Ω /10K Ω		246x174x110	
	MS-15	15W	250Hz-17KHz	97dB	660 Ω /1K Ω /2K Ω		286x200x130	
MS-30	30W	220Hz-18KHz	330 Ω /500 Ω /1K Ω					
Wall Speaker	CF-60	2 Way	60W	120Hz-20KHz	85dB		8 Ω /166 Ω /333 Ω /660 Ω	226x327x163
	CF-120		120W				8 Ω /83 Ω /166 Ω /333 Ω	
	IWS-10	1 Way	10W	220Hz-12KHz	90dB	1K Ω /3.3K Ω	179x312x109	
	SWS-03	3W	220Hz-14KHz	93dB	3.3K Ω /5K Ω /10K Ω	182x274x120		
	SWS-10	10W	160Hz-10KHz	91dB	1K Ω /2K Ω /3.3K Ω			
	WS-203	3W	200Hz-16KHz	93dB	3.3K Ω /5K Ω /10K Ω	315x183x124		
	WS-210	10W					92dB	1K Ω /2K Ω /3.3K Ω
WS-230	30W	93dB					330 Ω /500 Ω /1K Ω	
Surface Mounted Speaker	FS-30N	1 Way	30W	100Hz-12KHz	89dB	8 Ω /330 Ω	177x302x163	
	FS-60N		60W			8 Ω /167 Ω		
	FS-100N		100W			8 Ω /100 Ω		
	FS-52N	2 Way	50W	55Hz-20KHz	86dB	8 Ω /200 Ω	143x230x145	
	CI-40(T)		20W	55Hz-15KHz	87dB	8 Ω /500 Ω (T)		
CI-60(T)	30W	55Hz-22KHz	88dB	8 Ω /333 Ω (T)				
Horn Speaker	CH-522	1 Way	20W	140Hz-12KHz	91dB	500 Ω /1K Ω	294x209x326	
	CH-532		30W	180Hz-9KHz	93dB	165 Ω /333 Ω		
	HS-20		20W	350Hz-5.5KHz	106dB	500 Ω /1K Ω	250 ϕ x280	
	HS-30		30W	250Hz-5KHz		330 Ω /660 Ω	280 ϕ x330	
	HS-50		50W	250Hz-5KHz		200 Ω /400 Ω	320 ϕ x350	
	HS-20RT		20W	350Hz-5KHz	104dB	500 Ω /1K Ω	250x197.5x310	
	HS-30RT		30W	250Hz-5KHz	106dB	330 Ω /660 Ω	320x210x365	
HS-40RT	40W	250Hz-5KHz	200 Ω /400 Ω	320x210x365				

Inter-M Corp. (IMK)

653-5 Banghak-Dong, Dobong-Ku, Seoul, Korea

Overseas Sales Team

Tel_ +82-2-2289-8141~7 Fax_ +82-2-2289-8149 E-mail_ overseas@inter-m.com

www.inter-m.com

※ Design and specification are subject to be changed without pre notice.